



DIMENSIONS AND FEATURES						PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	h min.-max.	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
M 2.0	2.20-2.45	4.13-4.87	0.27-0.33	0.50-1.00	0.030	5000	280000	1000
M 2.3	2.50-2.75	4.63-5.37	0.27-0.33	0.50-1.00	0.035	5000	240000	1000
M 2.6	2.80-3.05	5.13-5.87	0.27-0.33	0.55-1.10	0.029	5000	200000	1000
M 3.0	3.20-3.50	5.63-6.37	0.35-0.45	0.65-1.30	0.053	2000	170000	500
M 3.5	3.70-4.00	6.55-7.45	0.35-0.45	0.70-1.40	0.070	2000	110000	500
M 4.0	4.30-4.60	7.55-8.45	0.45-0.55	0.80-1.60	0.130	2000	75000	500
M 5.0	5.30-5.60	9.55-10.45	0.45-0.55	0.90-1.80	0.206	1000	35000	200
M 6.0	6.40-6.76	10.45-11.55	0.45-0.55	1.10-2.20	0.235	1000	32000	200
M 7.0	7.40-7.76	11.45-12.55	0.45-0.55	1.20-2.40	0.265	1000	30000	200
M 8.0	8.40-8.76	14.45-15.55	0.45-0.55	1.70-3.40	0.476	1000	15000	200
M 10.0	10.50-10.93	17.45-18.55	0.74-0.86	2.00-4.00	1.050	1000	8500	100

Dimensions in mm

Technical details:

Hardness: 430 - 530 Hv.
 Tightening couples: see table.
 Chemical analysis of raw material: see table.

Anticorrosion surface covering:

Burnishing and light oiling.
 Electrozinc plating 6-8 my Cr6 free.
 White mech. zinc plating 12my Cr6 free.
 Other finishings by request.

Features and specific use:

Spring washer with reduced thickness and outside diameter for light applications and limited tightening couples.