



DIMENSIONS AND FEATURES							PACKAGING		
For screws of	d min.-max.	Side 1 min.-max.	Side 2 min.-max.	s min.-max.	h min.-max.	Kg/1000 pieces	N° of pcs standard packaging	N° of pcs bulk packaging	N° of pcs micro packaging
M 3.0	3.20-3.50	5.90-6.10	6.85-7.15	1.10-1.30	2.40-2.60	0.300		40000	
M 3.5	3.70-4.00	6.90-7.10	8.35-8.65	1.36-1.44	2.90-3.10	0.510		22500	
M 4.0	4.30-4.60	7.90-8.10	9.85-10.15	1.40-1.60	2.90-3.10	0.740		17500	
M 5.0	5.30-5.60	11.30-11.70	13.80-14.20	1.60-1.80	4.10-4.30	1.860		7500	
M 6.0	6.40-6.76	18.30-18.70	19.80-20.20	2.40-2.60	6.10-6.30	6.675		2000	

Dimensions in mm

Technical details:

Hardness: 415 - 490 Hv
 Tightening couples: see table.
 Chemical analysis of raw material : see table.

Anticorrosion surface covering:

Dry and clean surface.
 Other finishings by request.

Features and specific use:

To be used in the electrical contact industry.