



STAINLESS STEEL AISI 304 EN 10088-2

DIMENSIONS AND FEATURES						PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	h min.-max.	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
M 2.0	2.20-2.45	4.70-5.00	0.37-0.43	0.50-0.60	0.050	5000		1000
M 2.5	2.70-2.95	5.70-6.00	0.47-0.53	0.61-0.72	0.074	5000		1000
M 3.0	3.20-3.50	6.64-7.00	0.57-0.63	0.72-0.85	0.125	2000		500
M 3.5	3.70-4.00	7.64-8.00	0.77-0.83	0.92-1.06	0.250	2000		500
M 4.0	4.30-4.60	8.64-9.00	0.96-1.04	1.12-1.30	0.380	2000		500
M 5.0	5.30-5.60	10.57-11.00	1.16-1.24	1.35-1.55	0.620	1000		200
M 6.0	6.40-6.76	13.57-14.00	1.46-1.54	1.70-2.00	1.523	1000		200
M 7.0	7.40-7.76	16.57-17.00	1.70-1.80	2.00-2.30	2.530	1000		100
M 8.0	8.40-8.76	17.57-18.00	1.95-2.05	2.24-2.60	2.850	1000		100
M 10.0	10.50-10.93	22.48-23.00	2.45-2.55	2.80-3.20	6.450	500		100
M 12.0	13.00-13.43	28.48-29.00	2.94-3.06	3.43-3.95	12.400	250		50
M 14.0	15.00-15.43	34.38-35.00	3.44-3.56	4.04-4.65	21.441	200		
M 16.0	17.00-17.43	38.38-39.00	3.92-4.08	4.58-5.25	28.799	100		

Dimensions in mm

Technical details:

Hardness: 265 Hv minimum.

Tightening couples: see table.

Chemical analysis of raw material: see table.

Stainless steel AISI 304 (A2) guarantees a good corrosion resistance.

Features and specific use:

Stainless steel washer with the highest coefficient of elasticity for heavy applications with high tightening couples.

Recommended in case of breaking, settlements, erosion and differential expansion of the parts which constitute the assembling.