



### DOUBLE TOOTHED

**CARBON STEEL C 60 EN 10132**

DIMENSIONS AND FEATURES							PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	No. of internal teeth	No. of teeth	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
M 4.0	4.20-4.38	15.17-15.60	0.77-0.83	7	16	1.100	1000	6500	
M 5.0	5.10-5.28	17.47-17.90	0.77-0.83	7	16	1.450	1000	5000	
M 6.0	6.10-6.32	17.77-18.20	0.87-0.93	8	16	1.529	1000	4500	
M 8.0	8.20-8.42	21.73-22.25	0.96-1.04	10	16	2.490	500	2750	
M 10.0	10.20-10.47	25.58-26.10	1.06-1.14	12	18	4.150	500	1750	
M 12.0	12.50-12.77	29.78-30.30	1.16-1.24	12	18	5.400	200	1000	
M 16.0	16.30-16.73	35.48-36.10	1.36-1.44	12	20	8.699	250	800	

Dimensions in mm

#### Technical details:

Hardness: 430 - 510 Hv.  
 Tightening couples: see table.  
 Chemical analysis of raw material: see table.

#### Anticorrosion surface covering:

Burnishing and light oiling.  
 Electrozinc plating 6-8 cr6 free.  
 Mechanical zinc plating 12 my cr6 free.  
 Other finishings by request.

#### Features and specific use:

Double toothed washers.  
 Suitable when the diameter of the bore is larger than the diameter of the screw or when the bore is lengthened.