



DIMENSIONS AND FEATURES							PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	h min.-max.	No. of knurls	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
M 3.0	3.10-3.35	7.71-8.29	0.57-0.63	0.80-1.00	28	0.188	2000	60000	500
M 4.0	4.10-4.40	9.71-10.29	0.86-0.94	1.15-1.40	32	0.430	2000	25000	500
M 5.0	5.10-5.40	11.65-12.35	1.06-1.14	1.45-1.80	36	0.730	1000	15000	200
M 6.0	6.10-6.40	13.65-14.35	1.26-1.34	1.75-2.10	45	1.170	1000	10000	200
M 8.0	8.20-8.56	17.65-18.35	1.36-1.44	1.90-2.35	45	2.200	1000	5000	100
M 10.0	10.20-10.56	21.58-22.42	1.55-1.65	2.25-2.75	45	3.706	1000	3000	100
M 12.0	12.40-12.83	26.58-27.42	1.75-1.85	2.60-3.10	45	6.316	500	1750	50
M 14.0	14.40-14.83	29.58-30.42	2.34-2.46	3.20-3.70	45	9.800	250	1000	
M 16.0	16.40-16.83	31.50-32.50	2.74-2.86	3.60-4.10	60	12.500	250	900	
M 20.0	20.50-21.02	39.50-40.50	3.14-3.26	4.30-4.90	60	23.290	100	500	

Dimensions in mm

Technical details:

Hardness: 265 Hv minimum.

Tightening torques: see table.

Chemical analysis of raw material: see table.

Stainless steel AISI 304 (A2) has a good corrosion resistance. Stainless steel AISI 316 (A4) has a very high acid resistance and it is an antimagnetic material.

Features and specific use:

Stainless steel washer with elasticity that has a round, knurled ring with resistance to loosening on its contact surface with the screw's underhead. In every field of applications in which high resistance to loosening and elastic stress are required on large supporting surface.