



DIMENSIONS AND FEATURES							PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	h min.-max.	No. of knurls	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
M 4.0	4.10-4.40	13.65-14.35	0.96-1.04	1.40-1.80	32	1.102	2000		
M 5.0	5.10-5.40	15.65-16.35	1.16-1.24	1.70-2.10	36	1.650	1000		
M 6.0	6.10-6.40	17.65-18.35	1.36-1.44	2.10-2.50	45	2.466	1000		
M 8.0	8.20-8.56	21.58-22.42	1.55-1.65	2.20-2.70	45	4.085	1000		
M 10.0	10.20-10.56	26.58-27.42	1.75-1.85	2.60-3.10	45	6.938	500		
M 12.0	12.40-12.83	31.50-32.50	1.95-2.05	3.10-3.60	45	10.694	250		

Dimensions in mm

Technical details:

Hardness: 265 Hv minimum.

Tightening torques: see table.

Chemical analysis of raw material: see table.

Stainless steel AISI 304 (A2) guarantees a good corrosion resistance.

Features and specific use:

Stainless steel washer with elasticity that has a round, knurled ring with resistance to loosening on its contact surface with the screw's underhead. In every field of applications in which high resistances to loosening and elastic stress are required on soft surfaces (plastic, aluminium, etc...).